

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):


- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A61B 5/11, 5/0205, G08B 21/00	A1	(11) International Publication Number: WO 93/16636 (43) International Publication Date: 2 September 1993 (02.09.93)
(21) International Application Number: PCT/FI93/00067 (22) International Filing Date: 26 February 1993 (26.02.93) (30) Priority data: 920896 28 February 1992 (28.02.92) FI (71)(72) Applicant and Inventor: MYLLYMÄKI, Matti [FI/FI]; Sisämaantie 18 A, SF-02610 Espoo (FI). (74) Agent: LEITZINGER OY; Ruoholahdenkatu 8, SF-00180 Helsinki (FI). (81) Designated States: AT, AU, BB, BG, BR, CA, CH, CZ, DE, DK, ES, FI, GB, HU, JP, KP, KR, LK, LU, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SK, UA, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI pa- tent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, SN, TD, TG).		Published <i>With international search report.</i>
(54) Title: WRIST-HELD MONITORING DEVICE FOR PHYSICAL CONDITION  (57) Abstract The invention relates to a monitoring device for physical condition, including a wrist-held detector and transmitter unit (1) and at least one separate receiver (2), to which a surveillance message or an alarm is delivered by means of a radio frequency message. The detector means include a sensor (4) for physiological condition and an acceleration sensor (5) which controls a fuzzy logic (7) such that, depending on the movement activity, sliding alarm limits are set for the physical condition sensor (4).		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

Wrist-held monitoring device for physical condition

The present invention relates to a wrist-held monitoring device for independently observing the physical condition of a person by means of motoric activity and physiological condition, e.g., temperature and/or electric conductivity of the skin. The anomalous condition data is transmitted by conventional technique on a radio frequency message to one or more receivers, which either set off a local alarm or the data is transferred by conventional technique to a centralized receiving point for alarms.

A wrist-held device for the independent and on-line surveillance of movement and physical condition is not yet in sight. Traditionally, the surveillance has been effected by using extra-personal sensors, e.g. by monitoring the use of a door. The problems include a long monitoring time, high installation costs as well as false alarms as a person under surveillance leaves the space without switching off the surveillance. There are also portable radio transmitters provided with a switch for indicating the posture of a person; a problem with such devices are false alarms as the user must remember to take off the device when lying down. Another problem is that the surveillance is only active when a person is on his or her feet. Prior known is also monitoring of the heart, but that does not provide information about motoric activity and is not suitable for motion control. The heart monitoring devices are also traditionally expensive and require a frequent battery replacement and are not suitable for applications with a lot of users in a restricted area or when a long-time surveillance is required.

An object of the invention is to provide a wrist-watch type of device, which the carrier wears constantly in his or her wrist and which monitors physical condition independently and on-line

as well as issues an alarm upon detecting an abnormal situation. This object is achieved with the invention on the basis of the characterizing features set forth in the appended claim 1. The wrist-held device delivers an alarm, which carries an ID-code specifying the transmitting device, to a separate receiver or a plurality of receivers which can even cover an entire hospital or region. The receivers can be connected to various local alarms or to an emergency phone. The device may offer the user a conventional chance to set off a self-induced alarm with a press button. The physical condition surveillance by means of the motoric activity and physiological condition is, however, the main function of the device. The device is capable of achieving a so-called functional time surveillance for the elderly, i.e. incidents that a person being monitored falls, loses consciousness or ability to move will be identified and the device automatically produces an alarm. The wrist alarm is also suitable for the surveillance of wandering dementia patient as well as for use as assault alarms. All active deductions and the processing of sensor messages take place in the wrist alarm with a simple and very low-current technique, the device being operable for very long periods on the same batteries.

The invention will now be described in more detail with reference made to the accompanying drawings, in which

Fig. 1 shows a device of the invention, including a wrist-held detector and transmitter unit 1 and a separate receiver unit 2.

Fig. 2 is a bottom view of the detector and transmitter unit.

Fig. 3 shows a general block diagram for a device of the invention.

Fig. 4 shows how fuzzy logic is applied to interpret the mutual dependency of the different sensors, and

Fig. 5 shows an example of a logical flow chart for signals and pulses associated with operation of the device.

A device of the invention includes a wrist-watch size detector and transmitter unit 1, whose bottom is fitted with silver-plated contact surfaces for a sensor 4 of temperature and/or electric conductivity of the skin. Alternatively or in addition, the sensor 4 may include a sensor which detects or indicates a heartbeat. Upon monitoring the heart operation, one heartbeat is sufficient during each watching period, whereby no pulse counting is made in order to reduce the current consumption. The device is also provided with an acceleration sensor 5, and a pulse detector 6 for the acceleration sensor, a counter 7A for counting the pulses from detector 6, a fuzzy logic 7 for handling or analysis the information from sensors 4 and 5, and a radio transmitter 9. The alarm conditions are interpreted on the basis of the sensor signals by means of the fuzzy logic as will be explained later. A separate receiver unit 2 is fitted with an alarm relay release 11 and a radio receiver 10.

The electric skin conductivity and/or temperature of skin is measured with contact surfaces of sensors 4. After A/D transformation, the signal from sensor 4 is measured by counter 7B. By means of fuzzy logic 7, e.g. the electric skin conductivity may be used to control the counting rate of counter 7A in a manner that a high skin resistance decelerates the counter 7A and a low skin resistance accelerates the counter 7A, thereby defining sliding alarm limits. In a typical case (Fig. 4), however, the fuzzy logic 7 controls the mutual dependency of the different sensors 4 and 5 such that by means of a signal from acceleration sensor (5) an estimate of movement

activity is made, and this estimate is used to determine the sliding alarm limits (Min and Max) for signals from sensor(s) 4. If the counting value of counter 7B for one or more of the sensors 4 falls outside said sliding alarm limits (Min and Max), then an alarm is caused first in an alarm unit 12 of the wrist held device and, if the alarm is not quitted in a predetermined time by button 13, then the alarm is transmitted to receiver 2/10. If the counting value(s) of counter 7B is (are) within said limits, then the counters 7A, 7B are reset to zero for a new watching period.

Acceleration sensor 5 detects the hand movements and uses pulse detector 6 also to deliver a pulse to the fuzzy logic whenever a sufficiently extensive movement is detected. If it is not reset to zero within a determined period of time, the counter 7A will switch on radio transmitter 9 which sends an alarm to receiver 10. So, in addition to the general movement activity, the acceleration sensor 5 may be used to indicate the rate of acceleration of individual hand movements.

A counter 8 is used to count a predetermined number of pulses delivered by the acceleration sensor 5 so as to switch on radio transmitter 9 and to send a so-called dementia message reporting that a monitored person is moving. If a receiver defining the area to be monitored receives such a message, an alarm will be released. When a user takes off the wrist alarm, the contact surfaces measuring electric conductivity and/or temperature of the skin set the counter rate to such a slow level that an alarm is not released if a user removes the device e.g. when having a shower or sauna. When leaving home, the device is retained in the wrist and, thus, false alarms are not produced as a result of even a long absence.

An example of the logical operation of wrist alarm 1 and detectable factors of the device are illustrated in fig. 5. In

this case, the controlling signal for a wrist alarm is electric conductivity of the skin, which is obtained from contact surfaces 4 controlling the rate of counter 7A, whereby a high electric conductivity of the skin results in the counter reaching an alarm threshold 8 more quickly, the alarm switching on radio transmitter 9. When a user is moving his or her hand, the acceleration sensor 5 delivers a reset pulse to counter 7A and counting is started from the beginning. Counter 8 transmits a dementia message after receiving a sufficient number of pulses.

Claims

1. A monitoring device for physical condition, including a wrist-held detector and transmitter unit (1), fitted with detector means (4, 5) for monitoring physical condition and a radio transmitter (9) for delivering a surveillance or alarm signal, as well as at least one separate receiver (2) for delivering either a local surveillance message or an alarm, or the surveillance message or the alarm is transferred to a centralized receiving point for alarms, c h a r a c t e r - i z e d in that said detector means include:

-at least one sensor (4) for monitoring physiological condition which includes at least one of the following conditions: temperature of the skin, electric conductivity of the skin and heartbeat;

-sensor (5) for detecting the hand movements; and

-fuzzy logic (7) for controlling the mutual dependency of the outputs from said sensors (4,5) such that the output from one of the sensors (e.g. 5) sets sliding alarm limits for the output from the other of said sensors (e.g. 4).

2. A device as set forth in claim 1, c h a r a c t e r i z e d in that the output from said movement activity sensor (5) determines said sliding alarm limits for the output from said physiological condition sensor (4).

3. A device as set forth in claim 1 or 2, c h a r a c t e r - i z e d in that the output from said physiological condition sensor (4) includes at least two signals, each representing one of said physiological conditions, whereby an alarm is triggered on if one of said two signals falls outside said sliding alarm limits.

4. A device as set forth in claim 1, characterized in that between the sensors (4,5) and said fuzzy logic (7) there is at least one counter (7A,7B) which switches on radio transmitter (9), which sends an alarm to a receiver (10) if said counter (7A; 7B) is not reset within a predetermined period of time.



5. A device as set forth in claim 1, characterized in that said detector and transmitter unit (1) further includes a counter (8) for counting a predetermined number of pulses delivered by said movement activity sensor (5) so as to switch on radio transmitter (9) and to send out a so-called dementia message indicating that a monitored person is moving.



6. A device as set forth in claim 1, characterized in that said physiological condition sensor (4) includes a measuring sensor (4) for electric conductivity of the skin and is also provided with a temperature measuring sensor.


7. A device as set forth in claim 1, characterized in that a high electric resistance of the skin decelerates a counter (7A) between the movement activity sensor (5) and the fuzzy logic (7) and a low electric resistance of the skin accelerates said counter (7A).

8. A device as set forth in any of the claims 1, 2, 3 or 4, characterized in that the movement activity sensor (5) is an acceleration sensor.

9. A device as set forth in claim 8, characterized in that in addition to the general movement activity, said acceleration sensor (5) indicates the rate of acceleration of individual hand movements.

**Fig. 1****Fig. 2**

**Fig. 3****Fig. 4**

**Fig. 5**

A. CLASSIFICATION OF SUBJECT MATTER

IPC5: A61B 5/11, A61B 5/0205, G08B 21/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC5: A61B, G08B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

ORBIT: WPI, CLAIMS

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 4819860 (JAMES L. HARGROVE ET AL), 11 April 1989 (11.04.89), column 1, line 47 - column 2, line 3 --	1-9
A	US, A, 4952928 (GARY T CARROLL ET AL), 28 August 1990 (28.08.90), abstract --	1-9
A	US, A, 4958645 (THEODORE E. CADELL ET AL), 25 Sept 1990 (25.09.90) --	1-9
A	US, A, 4938228 (WILLIAM H. RIGHTER ET AL), 3 July 1990 (03.07.90), claims 1-8 --	1

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "B" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

7 June 1993

Date of mailing of the international search report

10 -06- 1993

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Anders Holmberg
Telephone No. +46 8 782 25 00

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 5025791 (MINORU NIWA), 25 June 1991 (25.06.91), column 1, line 66 - column 2, line 13 --	1
A	US, A, 4052979 (MARY ANN SCHERR ET AL), 11 October 1977 (11.10.77), column 1, line 59 - column 2, line 47 -- -----	1

30/04/93

PCT/FI 93/00067

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US-A-	4819860	11/04/89	NONE		
US-A-	4952928	28/08/90	EP-A-	0357309	07/03/90
US-A-	4958645	25/09/90	NONE		
US-A-	4938228	03/07/90	AU-A-	5197990	05/09/90
			EP-A-	0458896	04/12/91
US-A-	5025791	25/06/91	JP-A-	2258576	19/10/90
US-A-	4052979	11/10/77	NONE		

